

# GF TOP

Saw blade lubricating compound

The life-extension-fluid for your bevelers and saw blades.

Increases the saw blade life-time.

The lubrication is a synthetic high-performance lubricant for cutting and beveling.

Your benefits:

- High tool life
- Reduced tool costs
- Silicon-free



GF TOP is equipped with a little screw on brush to precisely apply the lubricant onto the tool.

# Fine lubrication by Orbitalum Tools:



**GF TOP**  
**Synthetic high-performance lubricant** for cutting and beveling machines. Increases the tool life of the saw blade. Compliant with the food approval NSF H2. The screwable brush guarantees an easy and uniform application of lubricant on the saw blade. Tube, 180 g  
**Code 790 060 228**



**Cutting lubrication KSS TOP**  
The water soluble, fully synthetic cooling fluid extends the tool life of the tool bits. Contains no hazardous substances (no labelling requirements according to GefStoffV.). Fulfills DVGW requirements, regarding drinking water, work sheet W 521. Pump sprayer, 500 ml  
**Code 790 060 226**  
Refill canister, 10 l  
**Code 790 060 227**



**GF LUB**  
**Saw blade lubricant**  
The NEW chlorine-free high-performance lubricant for cutting and beveling. Increases the tool life of the saw blade. This ecologically cutting compound is the environmentally friendly replacement for ROCOL: just with a new name and improved quality. GF LUB meets the latest environmental directives and ecological standards. Tube, 160 ml  
**Code 790 041 016**



**Thread cutting compound NORMOLIC® S**  
For drinking-water installations according to SVGW regulations. Can, 10 l  
**Code 790 051 263**



**Special gearing oil**  
For all RA machines. Bottle, 250 ml  
**Code 790 041 030**



**Thread cutting compound SPN PARALIQU® PLUS**  
Pressure absorption capacity 4 times higher than required according to DVGW work sheet W 521 – highly increased service life of the chase. On synthetical basis for drinking-water installations and for the food industries, conforms to requirements regarding food and beverage stuff legislation set out in DVGW/SVGW/ÖVGW, environment friendly – readily biodegradable. Can, 10 l  
**Code 790 060 202**

Stamp of distributor:



**Thread jointing compound PARALIQU® PM 35**  
For gas, air and water up to 130 °C. Approved by the DVGW/SVGW/ÖVGW in accordance with DIN EN 751, part 2 (DIN 30 660) in the house installation, especially for drinking-water installations. For use with flax. Can, 600 g  
**Code 790 060 102**

© Orbitalum Tools GmbH (02.2010)